

## AC Current Probe Model MN193-BK

Cat. #2140.36

Measurement range:

**5A: 0.005 to 6A<sub>AC</sub>, 100A: 0.1 to 120A<sub>AC</sub>**

AC current probe for use with Models 3945/3945-B, 8220, 8230, 8333, 8335, 8336, PEL Series, L104 and L564.



Cat.#2140.36

Clamping Diameter	0.78" (20mm)
Current Range	5A & 100AAC
Measurement Range	5mA to 6A AC & 200mA to 120AAC
Lead Length	10 ft (3m)
Output Termination	Proprietary connector
Accuracy (Typical)	±1%
Power Source	N/A
Compatibility	AEMC PowerPads and PELs
Operating Temperature	14° to +131°F (-10° to +55°C); 10 to 85% RH
Storage Temperature	-40° to +158°F (-40° to +70 °C); 10 to 90% RH
Dimensions	5.47 x 2.0 x 1.18" (135 x 51 x 30mm)
Weight	24 oz (690g)
Pollution Degree	2
Protection	IK 04, IP40 (jaws closed), IP30 (jaws open)

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)

[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

